

PERMA-LASTIC

WATERPROOF PAINT

DESCRIPTION

Perma-Lastic is a waterproof elastic paint that prevents water penetration in floors and walls with permanent elasticity.

FEATURES

Perma-Lastic is suitable for the repair of fissures and cracks in mortar and concrete and acts as a sealant, ideal for roofs, terraces, cement tanks and external walls. It can also be applied on roofing sheets Galvanized, Aluminium etc.

Perma-Lastic is an easy-to-apply paint and once dry forms a protective sheet without joints and an impermeable elastic barrier.

APPLICATION

Stir the container well. The surface to be painted must be consistent, clean, dry and free of dust.

Use a paint roller or a paint brush.

It is recommended to apply three coats.

First coat: up to 20 % of water can be added mixed well and applied.

Second AND third coat: wait at least 8 hours and apply without the addition of water.

TECHNICAL DATA

Nature	Modified acrylic
Finish	Semi-Mate
Colour	Red, Grey, White
Density	1.20-1.40 Kg / liter
Coverage	8 m ² / kg
Drying at 23° C 60% RH	6-8 hours
Application methods	Brush, roller and gun
Dilution	Water

PACKAGING

Plastic bucket of 10 kgs.

Once the bucket is opened, use the product within one month. Always keep unused quantity in a tightly sealed container.

One year shelf life.

Note

Instructions of use are given based on our testing and knowledge and do not imply any commitment. Said instructions do not free the user from examining and verifying the product for its correct use. Manufacturer's liability is limited to the value of the used goods. Complaints must be accompanied with the original package to allow proper traceability.